

Article 3.O:

**FP-O, Floodplain Overlay District**

Article 3.O:  
**FP-O, Floodplain Overlay District**

**SECTION I - GENERAL PROVISIONS**Section 1.1 – Statutory Authorization and Purpose [44 CFR 59.22(a)(2)]

This ordinance is adopted pursuant to the authority granted to localities by Va. **Code** § 15.2 - 2280.

The purpose of these provisions is to prevent: the loss of life and property, the creation of health and safety hazards, the disruption of commerce and governmental services, the extraordinary and unnecessary expenditure of public funds for flood protection and relief, and the impairment of the tax base by

- A. regulating uses, activities, and development which, alone or in combination with other existing or future uses, activities, and development, will cause unacceptable increases in flood heights, velocities, and frequencies;
- B. restricting or prohibiting certain uses, activities, and development from locating within districts subject to flooding;
- C. requiring all those uses, activities, and developments that do occur in flood-prone districts to be protected and/or flood-proofed against flooding and flood damage; and,
- D. protecting individuals from buying land and structures which are unsuited for intended purposes because of flood hazards.

Section 1.2 – Applicability

These provisions shall apply to all privately and publicly owned lands within the jurisdiction of **The Town of Smithfield** and identified as areas of special flood hazard *identified by the community or* shown on the flood insurance rate map (FIRM) or included in the flood insurance study (FIS) that are provided to the **Town of Smithfield** by FEMA. **The flood insurance rate map panels specifically referenced by this ordinance and dated to take effect on December 2, 2015 include the following: 51093C0088 E, 51093C0135 E, 51093C0151 E, 51093C0152 E, 51093C0153 E, 51093C0154 E.**

Section 1.3 - Compliance and Liability

- A. No land shall hereafter be developed and no structure shall be located, relocated, constructed, reconstructed, enlarged, or structurally altered except in full compliance with the terms and provisions of this ordinance and any other applicable ordinances and regulations which apply to uses within the jurisdiction of this ordinance.
- B. The degree of flood protection sought by the provisions of this ordinance is considered reasonable for regulatory purposes and is based on acceptable engineering methods of study, but does not imply total flood protection. Larger floods may occur on rare occasions. Flood

heights may be increased by man-made or natural causes, such as ice jams and bridge openings restricted by debris. This ordinance does not imply that districts outside the floodplain district or land uses permitted within such district will be free from flooding or flood damages.

- C. This ordinance shall not create liability on the part of **The Town of Smithfield** or any officer or employee thereof for any flood damages that result from reliance on this ordinance or any administrative decision lawfully made thereunder.

Section 1.4 – Records [44 CFR 59.22(a)(9)(iii)]

Records of actions associated with administering this ordinance shall be kept on file and maintained by or under the direction of the Floodplain Administrator in perpetuity.

Section 1.5 - Abrogation and Greater Restrictions [44 CFR 60.1(b)]

To the extent that the provisions are more restrictive, this ordinance supersedes any ordinance currently in effect in flood-prone districts. To the extent that any other existing law or regulation is more restrictive or does not conflict it shall remain in full force and effect.

These regulations are not intended to repeal or abrogate any existing ordinances including subdivision regulations, zoning ordinances or building codes. In the event of a conflict between these regulations and any other ordinance, the more restrictive shall govern.

Section 1.6 - Severability

If any section, subsection, paragraph, sentence, clause, or phrase of this ordinance shall be declared invalid for any reason whatever, such decision shall not affect the remaining portions of this ordinance. The remaining portions shall remain in full force and effect; and for this purpose, the provisions of this ordinance are hereby declared to be severable.

Section 1.7 - Penalty for Violations [44 CFR 60.2(e)]

Any person who fails to comply with any of the requirements or provisions of this article or directions of the ~~director of planning~~ **Planning and Zoning Administrator** or any authorized employee of the **Town of Smithfield** shall be guilty of ~~the appropriate violation and subject to the penalties thereof~~ **a Class 1 Misdemeanor**.

The VA USBC addresses building code violations and the associated penalties in Section 104 and Section 115. Violations and associated penalties of the Zoning Ordinance of **The Town of Smithfield** are addressed in **Article 11: Section Q and Article 2: Section X** of the Zoning Ordinance.

In addition to the above penalties, all other actions are hereby reserved, including an action in equity for the proper enforcement of this article. The imposition of a fine or penalty for any violation of, or noncompliance with, this article shall not excuse the violation or noncompliance or permit it to continue; and all such persons shall be required to correct or remedy such violations within a reasonable time. Any structure constructed, reconstructed, enlarged, altered or relocated in noncompliance with this article may be declared by the **Town of Smithfield** to be a public nuisance and abatable as such. Flood insurance may be withheld from structures constructed in violation of this article.

**SECTION II - ADMINISTRATION****Section 2.1 - Designation of the Floodplain Administrator** [44 CFR 59.22(b)]

The ~~Floodplain Administrator~~ Planning and Zoning Administrator is hereby appointed to administer and implement these regulations and is referred to herein as the Floodplain Administrator. The Floodplain Administrator may:

- A. Do the work themselves. In the absence of a designated Floodplain Administrator, the duties are conducted by the Town of Smithfield chief executive officer.
- B. Delegate duties and responsibilities set forth in these regulations to qualified technical personnel, plan examiners, inspectors, and other employees.
- C. Enter into a written agreement or written contract with another community or private sector entity to administer specific provisions of these regulations. Administration of any part of these regulations by another entity shall not relieve the community of its responsibilities pursuant to the participation requirements of the National Flood Insurance Program as set forth in the Code of Federal Regulations at 44 C.F.R. Section 59.22.

**Section 2.2 - Duties and Responsibilities of the Floodplain Administrator** [44 CFR 60.3]

The duties and responsibilities of the Floodplain Administrator shall include but are not limited to:

- A. Review applications for permits to determine whether proposed activities will be located in the Special Flood Hazard Area (SFHA).
- B. Interpret floodplain boundaries and provide available base flood elevation and flood hazard information.
- C. Review applications to determine whether proposed activities will be reasonably safe from flooding and require new construction and substantial improvements to meet the requirements of these regulations.
- D. Review applications to determine whether all necessary permits have been obtained from the Federal, State or local agencies from which prior or concurrent approval is required; in particular, permits from state agencies for any construction, reconstruction, repair, or alteration of a dam, reservoir, or waterway obstruction (including bridges, culverts, structures), any alteration of a watercourse, or any change of the course, current, or cross section of a stream or body of water, including any change to the 100-year frequency floodplain of free-flowing non-tidal waters of the State.
- E. Verify that applicants proposing an alteration of a watercourse have notified adjacent communities, the Department of Conservation and Recreation (Division of Dam Safety and Floodplain Management), and other appropriate agencies (VADEQ, USACE) and have submitted copies of such notifications to FEMA.

- F. Advise applicants for new construction or substantial improvement of structures that are located within an area of the Coastal Barrier Resources System established by the Coastal Barrier Resources Act that Federal flood insurance is not available on such structures; areas subject to this limitation are shown on Flood Insurance Rate Maps as Coastal Barrier Resource System Areas (CBRS) or Otherwise Protected Areas (OPA).
- G. Approve applications and issue permits to develop in flood hazard areas if the provisions of these regulations have been met, or disapprove applications if the provisions of these regulations have not been met.
- H. Inspect or cause to be inspected, buildings, structures, and other development for which permits have been issued to determine compliance with these regulations or to determine if non-compliance has occurred or violations have been committed.
- I. Review Elevation Certificates and require incomplete or deficient certificates to be corrected.
- J. Submit to FEMA, or require applicants to submit to FEMA, data and information necessary to maintain FIRMs, including hydrologic and hydraulic engineering analyses prepared by or for the **Town of Smithfield**, within six months after such data and information becomes available if the analyses indicate changes in base flood elevations.
- K. Maintain and permanently keep records that are necessary for the administration of these regulations, including:
  - 1. Flood Insurance Studies, Flood Insurance Rate Maps (including historic studies and maps and current effective studies and maps) and Letters of Map Change; and
  - 2. Documentation supporting issuance and denial of permits, Elevation Certificates, documentation of the elevation (in relation to the datum on the FIRM) to which structures have been floodproofed, inspection records, other required design certifications, variances, and records of enforcement actions taken to correct violations of these regulations.
- L. Enforce the provisions of these regulations, investigate violations, issue notices of violations or stop work orders, and require permit holders to take corrective action.
- M. Advise the Board of Zoning Appeals regarding the intent of these regulations and, for each application for a variance, prepare a staff report and recommendation.
- N. Administer the requirements related to proposed work on existing buildings:
  - 1. Make determinations as to whether buildings and structures that are located in flood hazard areas and that are damaged by any cause have been substantially damaged.
  - 2. Make reasonable efforts to notify owners of substantially damaged structures of the need to obtain a permit to repair, rehabilitate, or reconstruct. Prohibit the non-compliant repair of substantially damaged buildings except for temporary emergency protective measures

necessary to secure a property or stabilize a building or structure to prevent additional damage.

- O. Undertake, as determined appropriate by the Floodplain Administrator due to the circumstances, other actions which may include but are not limited to: issuing press releases, public service announcements, and other public information materials related to permit requests and repair of damaged structures; coordinating with other Federal, State, and local agencies to assist with substantial damage determinations; providing owners of damaged structures information related to the proper repair of damaged structures in special flood hazard areas; and assisting property owners with documentation necessary to file claims for Increased Cost of Compliance coverage under NFIP flood insurance policies.
- P. Notify the Federal Emergency Management Agency when the corporate boundaries of the **Town of Smithfield** have been modified and:
  - 1. Provide a map that clearly delineates the new corporate boundaries or the new area for which the authority to regulate pursuant to these regulations has either been assumed or relinquished through annexation; and
  - 2. If the FIRM for any annexed area includes special flood hazard areas that have flood zones that have regulatory requirements that are not set forth in these regulations, prepare amendments to these regulations to adopt the FIRM and appropriate requirements, and submit the amendments to the governing body for adoption; such adoption shall take place at the same time as or prior to the date of annexation and a copy of the amended regulations shall be provided to Department of Conservation and Recreation (Division of Dam Safety and Floodplain Management) and FEMA.
- Q. Upon the request of FEMA, complete and submit a report concerning participation in the NFIP which may request information regarding the number of buildings in the SFHA, number of permits issued for development in the SFHA, and number of variances issued for development in the SFHA.
- R. It is the duty of the Community Floodplain Administrator to take into account flood, mudslide and flood-related erosion hazards, to the extent that they are known, in all official actions relating to land management and use throughout the entire jurisdictional area of the Community, whether or not those hazards have been specifically delineated geographically (e.g. via mapping or surveying).

#### Section 2.3 - Use and Interpretation of FIRMs [44 CFR 60.3]

The Floodplain Administrator shall make interpretations, where needed, as to the exact location of special flood hazard areas, floodplain boundaries, and floodway boundaries. The following shall apply to the use and interpretation of FIRMs and data:

- A. Where field surveyed topography indicates that adjacent ground elevations:

1. Are below the base flood elevation, even in areas not delineated as a special flood hazard area on a FIRM, the area shall be considered as special flood hazard area and subject to the requirements of these regulations;
  2. Are above the base flood elevation and the area is labeled as a SFHA on the FIRM, the area shall be regulated as special flood hazard area unless the applicant obtains a Letter of Map Change that removes the area from the SFHA.
- B. In FEMA-identified special flood hazard areas where base flood elevation and floodway data have not been identified and in areas where FEMA has not identified SFHAs, any other flood hazard data available from a Federal, State, or other source shall be reviewed and reasonably used.
- C. Base flood elevations and designated floodway boundaries on FIRMs and in FISs shall take precedence over base flood elevations and floodway boundaries by any other sources if such sources show reduced floodway widths and/or lower base flood elevations.
- D. Other sources of data shall be reasonably used if such sources show increased base flood elevations and/or larger floodway areas than are shown on FIRMs and in FISs.
- E. If a Preliminary Flood Insurance Rate Map and/or a Preliminary Flood Insurance Study has been provided by FEMA:
1. Upon the issuance of a Letter of Final Determination by FEMA, the preliminary flood hazard data shall be used and shall replace the flood hazard data previously provided from FEMA for the purposes of administering these regulations.
  2. Prior to the issuance of a Letter of Final Determination by FEMA, the use of preliminary flood hazard data shall be deemed the best available data pursuant to Section 3.1.A.3. and used where no base flood elevations and/or floodway areas are provided on the effective FIRM.
  3. Prior to issuance of a Letter of Final Determination by FEMA, the use of preliminary flood hazard data is permitted where the preliminary base flood elevations or floodway areas exceed the base flood elevations and/or designated floodway widths in existing flood hazard data provided by FEMA. Such preliminary data may be subject to change and/or appeal to FEMA.

#### Section 2.4 - Jurisdictional Boundary Changes [44 CFR 59.22, 65.3]

The County floodplain ordinance in effect on the date of annexation shall remain in effect and shall be enforced by the municipality for all annexed areas until the municipality adopts and enforces an ordinance which meets the requirements for participation in the National Flood Insurance Program. Municipalities with existing floodplain ordinances shall pass a resolution acknowledging and accepting responsibility for enforcing floodplain ordinance standards prior to annexation of any area containing identified flood

hazards. If the FIRM for any annexed area includes special flood hazard areas that have flood zones that have regulatory requirements that are not set forth in these regulations, prepare amendments to these regulations to adopt the FIRM and appropriate requirements, and submit the amendments to the governing body for adoption; such adoption shall take place at the same time as or prior to the date of annexation and a copy of the amended regulations shall be provided to Department of Conservation and Recreation (Division of Dam Safety and Floodplain Management) and FEMA.

In accordance with the Code of Federal Regulations, Title 44 Subpart (B) Section 59.22 (a) (9) (v) all NFIP participating communities must notify the Federal Insurance Administration and optionally the State Coordinating Office in writing whenever the boundaries of the community have been modified by annexation or the community has otherwise assumed or no longer has authority to adopt and enforce floodplain management regulations for a particular area.

In order that all Flood Insurance Rate Maps accurately represent the community's boundaries, a copy of a map of the community suitable for reproduction, clearly delineating the new corporate limits or new area for which the community has assumed or relinquished floodplain management regulatory authority must be included with the notification.

#### Section 2.5 - District Boundary Changes

The delineation of any of the Floodplain Districts may be revised by the **Town of Smithfield** where natural or man-made changes have occurred and/or where more detailed studies have been conducted or undertaken by the U. S. Army Corps of Engineers or other qualified agency, or an individual documents the need for such change. However, prior to any such change, approval must be obtained from the Federal Emergency Management Agency. A completed LOMR is a record of this approval.

#### Section 2.6 - Interpretation of District Boundaries

Initial interpretations of the boundaries of the Floodplain Districts shall be made by the **Zoning Officer Planning and Zoning Administrator**. Should a dispute arise concerning the boundaries of any of the Districts, the Board of Zoning Appeals shall make the necessary determination. The person questioning or contesting the location of the District boundary shall be given a reasonable opportunity to present his case to the Board and to submit his own technical evidence if he so desires.

#### Section 2.7 – Submitting Model Backed Technical Data [44 CFR 65.3]

A community's base flood elevations may increase or decrease resulting from physical changes affecting flooding conditions. As soon as practicable, but not later than six months after the date such information becomes available, a community shall notify the Federal Emergency Management Agency of the changes by submitting technical or scientific data. The community may submit data via a LOMR. Such a submission is necessary so that upon confirmation of those physical changes affecting flooding conditions, risk premium rates and flood plain management requirements will be based upon current data.

#### Section 2.8 – Letters of Map Revision



When development in the floodplain will cause or causes a change in the base flood elevation, the applicant, including state agencies, must notify FEMA by applying for a Conditional Letter of Map Revision and then a Letter of Map Revision.

Example cases:

- Any development that causes a rise in the base flood elevations within the floodway.
- Any development occurring in Zones A1-30 and AE without a designated floodway, which will cause a rise of more than one foot in the base flood elevation.
- Alteration or relocation of a stream (including but not limited to installing culverts and bridges) 44  
*Code of Federal Regulations §65.3 and §65.6(a)(12)*

## SECTION III - ESTABLISHMENT OF ZONING DISTRICTS

### Section 3.1 - Description of Special Flood Hazard Districts [44 CFR 59.1, 60.3]

#### A. Basis of Districts

The various special flood hazard districts shall include the SFHAs. The basis for the delineation of these districts shall be the FIS and the FIRM for **The Town of Smithfield** prepared by the Federal Emergency Management Agency, Federal Insurance Administration, dated **December 2, 2015**, and any subsequent revisions or amendments thereto.

The **Town of Smithfield** may identify and regulate local flood hazard or ponding areas that are not delineated on the FIRM. These areas may be delineated on a "Local Flood Hazard Map" using best available topographic data and locally derived information such as flood of record, historic high water marks or approximate study methodologies.

The boundaries of the SFHA Districts are established as shown on the FIRM which is declared to be a part of this ordinance and which shall be kept on file at the **Town of Smithfield** offices

1. The **Floodway District** is in an **AE Zone** and is delineated, for purposes of this ordinance, using the criterion that certain areas within the floodplain must be capable of carrying the waters of the one percent annual chance flood without increasing the water surface elevation of that flood more than one (1) foot at any point. ~~The areas included in this District are specifically defined in Table \_\_\_\_\_ of the above-referenced FIS and shown on the accompanying FIRM.~~

The following provisions shall apply within the Floodway District of an AE zone [44 CFR 60.3(d)]:

- a. Within any floodway area, no encroachments, including fill, new construction, substantial improvements, or other development shall be permitted unless it has been demonstrated through hydrologic and hydraulic analysis performed in accordance with standard engineering practice that the proposed encroachment will not result in any increase in flood levels within the community during the occurrence of the base flood discharge. Hydrologic and hydraulic analyses shall be undertaken only by professional engineers or others of demonstrated qualifications, who shall certify that the technical methods used correctly reflect currently-accepted technical concepts. Studies, analyses, computations, etc., shall be submitted in sufficient detail to allow a thorough review by the Floodplain Administrator.

Development activities which increase the water surface elevation of the base flood may be allowed, provided that the applicant first applies – with the **Town of Smithfield** endorsement – for a Conditional Letter of Map Revision (CLOMR), and receives the approval of the Federal Emergency Management Agency.

If Article III Section 3.1 A 1 a is satisfied, all new construction and substantial improvements shall comply with all applicable flood hazard reduction provisions of Article 4.

b. The placement of manufactured homes (mobile homes) is prohibited, except in an existing manufactured home (mobile home) park or subdivision. A replacement manufactured home may be placed on a lot in an existing manufactured home park or subdivision provided the anchoring, elevation, and encroachment standards are met.

2. The **AE, ~~or AH~~ Zones** on the FIRM accompanying the FIS shall be those areas for which one-percent annual chance flood elevations have been provided and the floodway has **not** been delineated. The following provisions shall apply within an AE ~~or AH~~ zone [44 CFR 60.3(c)] where FEMA has provided base flood elevations **(The requirement in 60.3(c)(10) only applies along rivers, streams, and other watercourses where FEMA has provided base flood elevations. The requirement does not apply along lakes, bays and estuaries, and the ocean coast.):**

Until a regulatory floodway is designated, no new construction, substantial improvements, or other development (including fill) shall be permitted within the areas of special flood hazard, designated as Zones A1-30, ~~or AE, or AH~~ on the FIRM, unless it is demonstrated that the cumulative effect of the proposed development, when combined with all other existing and anticipated development, will not increase the water surface elevation of the base flood more than one foot at any point within the **Town of Smithfield**.

Development activities in Zones A1-30, ~~or AE, or AH~~ on the **Town of Smithfield** FIRM which increase the water surface elevation of the base flood by more than one foot may be allowed, provided that the applicant first applies – with the **Town of Smithfield** endorsement – for a Conditional Letter of Map Revision, and receives the approval of the Federal Emergency Management Agency.

3. The **A Zone** on the FIRM accompanying the FIS shall be those areas for which no detailed flood profiles or elevations are provided, but the one percent annual chance floodplain boundary has been approximated. For these areas, the following provisions shall apply [44 CFR 60.3(b)]:

The Approximated Floodplain District shall be that floodplain area for which no detailed flood profiles or elevations are provided, but where a one percent annual chance floodplain boundary has been approximated. Such areas are shown as Zone A on the maps accompanying the FIS. For these areas, the base flood elevations and floodway information from federal, state, and other acceptable sources shall be used, when available. Where the specific one percent annual chance flood elevation cannot be determined for this area using other sources of data, such as the U. S. Army Corps of Engineers Floodplain Information Reports, U. S. Geological Survey Flood-Prone Quadrangles, etc., then the applicant for the proposed use, development and/or activity shall determine this base flood elevation. For development proposed in the approximate floodplain the applicant must use technical methods that correctly reflect currently accepted practices, such as point on boundary, high

water marks, or detailed methodologies hydrologic and hydraulic analyses. Studies, analyses, computations, etc., shall be submitted in sufficient detail to allow a thorough review by the Floodplain Administrator.

The Floodplain Administrator reserves the right to require a hydrologic and hydraulic analysis for any development. When such base flood elevation data is utilized, the lowest floor shall be elevated to or above the base flood level plus eighteen (18) inches.

During the permitting process, the Floodplain Administrator shall obtain:

1. The elevation of the lowest floor (in relation to mean sea level), including the basement, of all new and substantially improved structures; and,
2. If the structure has been flood-proofed in accordance with the requirements of this article, the elevation (in relation to mean sea level) to which the structure has been flood-proofed.

Base flood elevation data shall be obtained from other sources or developed using detailed methodologies comparable to those contained in a FIS for subdivision proposals and other proposed development proposals (including manufactured home parks and subdivisions) that exceed fifty (50) lots or five (5) acres, whichever is the lesser.

~~4. The AO Zone on the FIRM accompanying the FIS shall be those areas of shallow flooding identified as AO on the FIRM. For these areas, the following provisions shall apply [44 CFR 60.3(e)]:~~

~~a. All new construction and substantial improvements of residential structures shall have the lowest floor, including basement, elevated to or above the flood depth specified on the FIRM, above the highest adjacent grade at least as high as the depth number specified in feet on the FIRM. If no flood depth number is specified, the lowest floor, including basement, shall be elevated no less than two feet above the highest adjacent grade.~~

~~b. All new construction and substantial improvements of non-residential structures shall~~

~~1) have the lowest floor, including basement, elevated to or above the flood depth specified on the FIRM, above the highest adjacent grade at least as high as the depth number specified in feet on the FIRM. If no flood depth number is specified, the lowest floor, including basement, shall be elevated at least two feet above the highest adjacent grade; or,~~

~~2) together with attendant utility and sanitary facilities be completely flood-proofed to the specified flood level so that any space below that level is watertight with walls substantially impermeable to the passage of water and with structural components having the capability of resisting hydrostatic and hydrodynamic loads and effects of~~

~~buoyancy.~~

~~c. Adequate drainage paths around structures on slopes shall be provided to guide floodwaters around and away from proposed structures.~~

5. The **Coastal A Zone** is labelled as AE on the FIRM; it is those areas that are seaward of the limit of moderate wave action (LiMWA) line. As defined by the VA USBC, these areas are subject to wave heights between 1.5 feet and 3 feet. For these areas, the following provisions shall apply:

Buildings and structures within this zone shall have the lowest floor elevated to or above the base flood elevation plus ~~one foot~~ **eighteen (18) inches** of freeboard, and must comply with the provisions in Article III, Section 3.1 A 2 and Article IV, Sections 4.2 and 4.3.

6. The **VE or V Zones** on FIRMs accompanying the FIS shall be those areas that are known as Coastal High Hazard areas, extending from offshore to the inland limit of a primary frontal dune along an open coast or other areas subject to high velocity waves. For these areas, the following provisions shall apply [44 CFR 60.3(e)]:

- a. All new construction and substantial improvements in Zones V and VE, including manufactured homes, shall be elevated on pilings or columns so that:
  - 1) The bottom of the lowest horizontal structural member of the lowest floor (excluding the pilings or columns) is elevated to or above the base flood level **plus eighteen (18) inches**; ~~if the lowest horizontal structural member is parallel to the direction of wave approach or elevated at least two feet above the base flood level if the lowest horizontal structural member is perpendicular to the direction of wave approach~~; and,
  - 2) The pile or column foundation and structure attached thereto is anchored to resist flotation, collapse, and lateral movement due to the effects of wind and water loads acting simultaneously on all building components. Wind and water loading values shall each have a one percent chance of being equaled or exceeded in any given year (one-percent annual chance).
- b. A registered professional engineer or architect shall develop or review the structural design, specifications and plans for the construction, and shall certify that the design and methods of construction to be used are in accordance with accepted standards of practice for meeting the provisions of Article III, Section A 6 a.
- c. The Floodplain Administrator shall obtain the elevation (in relation to mean sea level) of the bottom of the lowest horizontal structural member of the lowest floor (excluding pilings and columns) of all new and substantially improved structures in Zones V and VE. The Floodplain Management Administrator shall maintain a record of all such information.

- d. All new construction shall be located landward of the reach of mean high tide.
  - e. All new construction and substantial improvements shall have the space below the lowest floor either free of obstruction or constructed with nonsupporting breakaway walls, open wood-lattice work, or insect screening intended to collapse under wind and water loads without causing collapse, displacement, or other structural damage to the elevated portion of the building or supporting foundation system. For the purpose of this section, a breakaway wall shall have a design safe loading resistance of not less than 10 and no more than 20 pounds per square foot. Use of breakaway walls which exceed a design safe loading resistance of 20 pounds per square foot (either by design or when so required by local codes) may be permitted only if a registered professional engineer or architect certifies that the designs proposed meet the following conditions:
    - 1) Breakaway wall collapse shall result from water load less than that which would occur during the base flood; and
    - 2) The elevated portion of the building and supporting foundation system shall not be subject to collapse, displacement, or other structural damage due to the effects of wind and water loads acting simultaneously on all building components (structural and nonstructural). Maximum wind and water loading values to be used in this determination shall each have a one percent chance of being equaled or exceeded in any give year.
  - f. The enclosed space below the lowest floor shall be used solely for parking of vehicles, building access, or storage. Such space shall not be partitioned into multiple rooms, temperature-controlled, or used for human habitation. *The enclosed space ~~shall~~ should be less than 299 square feet (to avoid triggering high insurance rates).*
  - g. The use of fill for structural support of buildings is prohibited. When non-structural fill is proposed in a coastal high hazard area, appropriate engineering analyses shall be conducted to evaluate the impacts of the fill prior to issuance of a development permit.
  - h. The man-made alteration of sand dunes, which would increase potential flood damage, is prohibited.
7. *The mapped floodplain includes all of the above regions and also the regions designated as having a 0.2 percent annual chance of flooding on any flood map or flood insurance study. In this area no emergency service, medical service or governmental records storage ~~shall~~ should be allowed except by special exception using the variance process.*

### Section 3.2 - Overlay Concept

The Floodplain Districts described above shall be overlays to the existing underlying districts as shown on

the Official Zoning Ordinance Map, and as such, the provisions for the floodplain districts shall serve as a supplement to the underlying district provisions.

If there is any conflict between the provisions or requirements of the Floodplain Districts and those of any underlying district, the more restrictive provisions and/or those pertaining to the floodplain districts shall apply.

In the event any provision concerning a Floodplain District is declared inapplicable as a result of any legislative or administrative actions or judicial decision, the basic underlying provisions shall remain applicable.

#### **SECTION IV - DISTRICT PROVISIONS** [44 CFR 59.22, 60.2, 60.3]

##### Section 4.1 – Permit and Application Requirements

###### **A. Permit Requirement**

All uses, activities, and development occurring within any floodplain district, including placement of manufactured homes, shall be undertaken only upon the issuance of a zoning permit. Such development shall be undertaken only in strict compliance with the provisions of this Ordinance and with all other applicable codes and ordinances, as amended, such as the Virginia Uniform Statewide Building Code (VA USBC) and the **Town of Smithfield Subdivision and Zoning Regulations**. Prior to the issuance of any such permit, the Floodplain Administrator shall require all applications to include compliance with all applicable state and federal laws and shall review all sites to assure they are reasonably safe from flooding. Under no circumstances shall any use, activity, and/or development adversely affect the capacity of the channels or floodways of any watercourse, drainage ditch, or any other drainage facility or system.

###### **B. Site Plans and Permit Applications**

All applications for development within any floodplain district and all building permits issued for the floodplain shall incorporate the following information:

1. The elevation of the Base Flood at the site.
2. The elevation of the lowest floor (including basement) or, in V zones, the lowest horizontal structural member.
3. For structures to be flood-proofed (non-residential only), the elevation to which the structure will be flood-proofed.
4. Topographic information showing existing and proposed ground elevations.

Section 4.2 - General Standards

The following provisions shall apply to all permits:

- A. New construction and substantial improvements shall be built according to this ordinance and the VA USBC, and anchored to prevent flotation, collapse or lateral movement of the structure.
- B. Manufactured homes shall be anchored to prevent flotation, collapse, or lateral movement. Methods of anchoring may include, but are not limited to, use of over-the-top or frame ties to ground anchors. This standard shall be in addition to and consistent with applicable state anchoring requirements for resisting wind forces.
- C. New construction and substantial improvements shall be constructed with materials and utility equipment resistant to flood damage.
- D. New construction or substantial improvements shall be constructed by methods and practices that minimize flood damage.
- E. Electrical, heating, ventilation, plumbing, air conditioning equipment and other service facilities, including duct work, shall be designed and/or located so as to prevent water from entering or accumulating within the components during conditions of flooding.
- F. New and replacement water supply systems shall be designed to minimize or eliminate infiltration of flood waters into the system.
- G. New and replacement sanitary sewage systems shall be designed to minimize or eliminate infiltration of flood waters into the systems and discharges from the systems into flood waters.
- H. On-site waste disposal systems shall be located and constructed to avoid impairment to them or contamination from them during flooding.

In addition to provisions A – H above, in all special flood hazard areas, the additional provisions shall apply:

- I. Prior to any proposed alteration or relocation of any channels or of any watercourse, stream, etc., within this jurisdiction a permit shall be obtained from the U. S. Corps of Engineers, the Virginia Department of Environmental Quality, and the Virginia Marine Resources Commission (a joint permit application is available from any of these organizations). Furthermore, in riverine areas, notification of the proposal shall be given by the applicant to all affected adjacent jurisdictions, the Department of Conservation and Recreation (Division of Dam Safety and Floodplain Management), other required agencies, and the Federal Emergency Management Agency.
- J. The flood carrying capacity within an altered or relocated portion of any watercourse shall be maintained.



Section 4.3 - Elevation and Construction Standards [44 CFR 60.3]

In all identified flood hazard areas where base flood elevations have been provided in the FIS or generated by a certified professional in accordance with Section 3.1 A 3, the following provisions shall apply:

A. Residential Construction

New construction or substantial improvement of any residential structure (including manufactured homes) in Zones A1-30, AE, ~~AH~~ and A with detailed base flood elevations shall have the lowest floor, including basement, elevated to or above the base flood level *plus eighteen(18) inches*. See Section 3.1.5 and Section 3.1.6 for requirements in the Coastal A and VE zones.

B. Non-Residential Construction

1. New construction or substantial improvement of any commercial, industrial, or non-residential building (or manufactured home) shall have the lowest floor, including basement, elevated to or above the base flood level *plus eighteen (18) inches*. See Section 3.1.5 and Section 3.1.6 for requirements in the Coastal A and VE zones.
2. Non-residential buildings located in all A1-30, ~~or AE, and AH~~ zones may be flood-proofed in lieu of being elevated provided that all areas of the building components below the elevation corresponding to the BFE *plus ~~two foot~~ eighteen (18) inches* are water tight with walls substantially impermeable to the passage of water, and use structural components having the capability of resisting hydrostatic and hydrodynamic loads and the effect of buoyancy. A registered professional engineer or architect shall certify that the standards of this subsection are satisfied. Such certification, including the specific elevation (in relation to mean sea level) to which such structures are floodproofed, shall be maintained by the ~~Town~~ *Clerk*.

C. Space Below the Lowest Floor

In zones A, AE, ~~AH, AO,~~ and A1-A30, fully enclosed areas, of new construction or substantially improved structures, which are below the regulatory flood protection elevation shall:

1. Not be designed or used for human habitation, but shall be used solely for parking of vehicles, building access, or limited storage of maintenance equipment used in connection with the premises. Access to the enclosed area shall be the minimum necessary to allow for parking of vehicles (garage door) or limited storage of maintenance equipment (standard exterior door), or entry to the living area (stairway or elevator).
2. be constructed entirely of flood resistant materials below the regulatory flood protection elevation;

3. include measures to automatically equalize hydrostatic flood forces on walls by allowing for the entry and exit of floodwaters. To meet this requirement, the openings must either be certified by a professional engineer or architect or meet the following minimum design criteria:
  - a. Provide a minimum of two openings on different sides of each enclosed area subject to flooding.
  - b. The total net area of all openings must be at least one (1) square inch for each square foot of enclosed area subject to flooding.
  - c. If a building has more than one enclosed area, each area must have openings to allow floodwaters to automatically enter and exit.
  - d. The bottom of all required openings shall be no higher than one (1) foot above the adjacent grade.
  - e. Openings may be equipped with screens, louvers, or other opening coverings or devices, provided they permit the automatic flow of floodwaters in both directions.
  - f. Foundation enclosures made of flexible skirting are not considered enclosures for regulatory purposes, and, therefore, do not require openings. Masonry or wood underpinning, regardless of structural status, is considered an enclosure and requires openings as outlined above.

D. Standards for Manufactured Homes and Recreational Vehicles

1. In zones A, AE, ~~AH, and AO~~, ~~VE and V~~, all manufactured homes placed, or substantially improved, on individual lots or parcels, must meet all the requirements for new construction, including the elevation and anchoring requirements in sections 3.1.A.6., 4.2, and 4.3.
2. All recreational vehicles placed on sites must either:
  - a. be on the site for fewer than 180 consecutive days, be fully licensed and ready for highway use (a recreational vehicle is ready for highway use if it is on its wheels or jacking system, is attached to the site only by quick disconnect type utilities and security devices and has no permanently attached additions); or
  - b. meet all the requirements for manufactured homes in Article 4.3(D)(1).

Section 4.4 - Standards for Subdivision Proposals

- A. All subdivision proposals shall be consistent with the need to minimize flood damage;

- B. All subdivision proposals shall have public utilities and facilities such as sewer, gas, electrical and water systems located and constructed to minimize flood damage;
- C. All subdivision proposals shall have adequate drainage provided to reduce exposure to flood hazards, and
- D. Base flood elevation data shall be obtained from other sources or developed using detailed methodologies, hydraulic and hydrologic analysis, comparable to those contained in a Flood Insurance Study for subdivision proposals and other proposed development proposals (including manufactured home parks and subdivisions) that exceed fifty (50) lots or five (5) acres, whichever is the lesser.

## **SECTION V – EXISTING STRUCTURES IN FLOODPLAIN AREAS**

Any structure or use of a structure or premises must be brought into conformity with these provisions when it is changed, repaired, or improved unless one of the following exceptions is established before the change is made:

- A. The floodplain manager has determined that
  - a. change is not a substantial repair or substantial improvement AND
  - b. no new square footage is being built in the floodplain that is not complaint AND
  - c. no new square footage is being built in the floodway AND
  - d. the change complies with this ordinance and the VA USBC AND
  - ~~e. the change, when added to all the changes made during a rolling 5-year period does not constitute 50% of the structure's value.~~
- B. The changes are required to comply with a citation for a health or safety violation.
- C. The structure is a historic structure and the change required would impair the historic nature of the structure.

**SECTION VI - VARIANCES: FACTORS TO BE CONSIDERED [44 CFR 60.6]**

Variances shall be issued only upon (i) a showing of good and sufficient cause, (ii) after the Board of Zoning Appeals has determined that failure to grant the variance would result in exceptional hardship to the applicant, and (iii) after the Board of Zoning Appeals has determined that the granting of such variance will not result in (a) unacceptable or prohibited increases in flood heights, (b) additional threats to public safety, (c) extraordinary public expense; and will not (d) create nuisances, (e) cause fraud or victimization of the public, or (f) conflict with local laws or ordinances.

While the granting of variances generally is limited to a lot size less than one-half acre, deviations from that limitation may occur. However, as the lot size increases beyond one-half acre, the technical justification required for issuing a variance increases. Variances may be issued by the Board of Zoning Appeals for new construction and substantial improvements to be erected on a lot of one-half acre or less in size contiguous to and surrounded by lots with existing structures constructed below the base flood level, in conformance with the provisions of this section.

Variances may be issued for new construction and substantial improvements and for other development necessary for the conduct of a functionally dependent use provided that the criteria of this section are met, and the structure or other development is protected by methods that minimize flood damages during the base flood and create no additional threats to public safety.

In passing upon applications for variances, the Board of Zoning Appeals shall satisfy all relevant factors and procedures specified in other sections of the zoning ordinance and consider the following additional factors:

- A. The danger to life and property due to increased flood heights or velocities caused by encroachments. No variance shall be granted for any proposed use, development, or activity within any Floodway District that will cause any increase in the one percent (1%) chance flood elevation.
- B. The danger that materials may be swept on to other lands or downstream to the injury of others.
- C. The proposed water supply and sanitation systems and the ability of these systems to prevent disease, contamination, and unsanitary conditions.
- D. The susceptibility of the proposed facility and its contents to flood damage and the effect of such damage on the individual owners.
- E. The importance of the services provided by the proposed facility to the community.
- F. The requirements of the facility for a waterfront location.

- G. The availability of alternative locations not subject to flooding for the proposed use.
- H. The compatibility of the proposed use with existing development and development anticipated in the foreseeable future.
- I. The relationship of the proposed use to the comprehensive plan and floodplain management program for the area.
- J. The safety of access by ordinary and emergency vehicles to the property in time of flood.
- K. The expected heights, velocity, duration, rate of rise, and sediment transport of the flood waters expected at the site.
- L. The historic nature of a structure. Variances for repair or rehabilitation of historic structures may be granted upon a determination that the proposed repair or rehabilitation will not preclude the structure's continued designation as a historic structure and the variance is the minimum necessary to preserve the historic character and design of the structure.
- M. Such other factors which are relevant to the purposes of this ordinance.

The Board of Zoning Appeals may refer any application and accompanying documentation pertaining to any request for a variance to any engineer or other qualified person or agency for technical assistance in evaluating the proposed project in relation to flood heights and velocities, and the adequacy of the plans for flood protection and other related matters.

Variances shall be issued only after the Board of Zoning Appeals has determined that the granting of such will not result in (a) unacceptable or prohibited increases in flood heights, (b) additional threats to public safety, (c) extraordinary public expense; and will not (d) create nuisances, (e) cause fraud or victimization of the public, or (f) conflict with local laws or ordinances.

Variances shall be issued only after the Board of Zoning Appeals has determined that the variance will be the minimum required to provide relief.

The Board of Zoning Appeals shall notify the applicant for a variance, in writing that the issuance of a variance to construct a structure below the one percent (1%) chance flood elevation (a) increases the risks to life and property and (b) will result in increased premium rates for flood insurance.

A record shall be maintained of the above notification as well as all variance actions, including justification for the issuance of the variances. Any variances that are issued shall be noted in the annual or biennial report submitted to the Federal Insurance Administrator.

**SECTION VII – ENACTMENT**

Enacted and ordained this \_\_\_\_ day of \_\_\_\_\_, 20\_\_\_\_. This ordinance, number \_\_\_\_ of **The Town of Smithfield**, Virginia, shall become effective upon passage.

\_\_\_\_\_  
Signature

\_\_\_\_\_  
Title

\_\_\_\_\_  
Attested